

Configuration

This service returns information about environment configuration.

NOTE:
The same parameters can also be obtained from any SDC device (E-SDC or V-SDC) which is the preferred option for obtaining this information - see [POS to SDC Protocol](#).

Endpoint

Endpoint	Example
<code><TaxCore_API_URL_obtained_from_certificate_as_e; here>/api/v3/configuration</code>	<code>https://api.suf.poreskaupravars.org/api/v</code>

NOTE:
Development and production environments, as well the environments in different countries, have different URLs. For this reason, URLs and names in your documentation, code and UI should not be hardcoded but configurable or extracted from a digital certificate.

HTTP Method

GET

Authentication

No authentication

Response

Field	Description
organizationName	Name of the tax authority organization
serverTimeZone	Time zone of the server location
street	Tax authority street address

city	Tax authority city
country	Tax authority country
endpoints	List of available endpoints
environmentName	Name of the environment
logo	Link to the tax authority's official logo
ntpServer	NTP server used for time synchronization
supportedLanguages	List of language-culture strings supported by TaxCore

Example

```
{
  "organizationName": "Data Tech International",
  "serverTimeZone": "Fiji Standard Time",
  "street": "Kruzni put 7",
  "city": "Belgrade",
  "country": "RS",
  "endpoints": {
    "taxpayerAdminPortal": "https://tap.sandbox.taxcore.dti.rs:443/",
    "taxCoreApi": "https://api.sandbox.taxcore.dti.rs:443/",
    "vsdc": "https://vsdc.sandbox.taxcore.dti.rs:443/",
    "root": "https://frontendui.sandbox.taxcore.dti.rs:443/v/?v1="
  },
  "environmentName": "SANDBOX",
  "logo": "https://i.imgur.com:443/tg5ad60.png?hash=315919327",
  "ntpServer": "http://0.europe.pool.ntp.org:80/",
  "supportedLanguages": [
    "en-US",
    "sr-Cyrl-RS"
  ]
}
```